

AGRICULTURAL MACHINERY I HYDRAULIC FLIP PLOW


LOVOL




PRODUCT INTRODUCTION

- Lovol hydraulic turnover plow performs extremely well in soft soil with or without sand and gravel to hard soil, and has a wide adaptability;
- Enlarging the auxiliary plough body makes the plowing and mulching performance better, and can achieve excellent stubble elimination effect;
- The plow beam adopts high-strength square tube to meet the operation requirements of the machine under heavy load conditions;
- The grid bar of the plough body is heat-treated and processed by wear-resistant alloy steel, and the tip of the plough is provided with tungsten carbide wear-resistant coating;
- Optional RS series double-acting amplitude modulation cylinder, the traction line adjustment of the flip plow is faster;


WEICHAI LOVOL INTELLIGENT AGRICULTURE



◀ The plow beam adopts high-strength square tube with high yield strength.



◀ Amplitude modulation cylinder of double-acting cylinder.



◀ The auxiliary plough body is enlarged, and the covering performance is excellent.



◀ Main plow body + auxiliary plow body, double shear safety bolts.

TECHNICAL PARAMETERS

Model	4405R	4405R	4506R
Product Model	L5D440-055	L5D440-050	L5B450-051
Mating Power/hp	150-180	150-180	200-240
Number of Plough Bodies	4+4	4+4	4+4
Tillage Width/cm	132-160	132-160	132-200
Tillage Depth/cm	20-35	20-35	20-35
Plough Body Spacing/cm	105	105	105
Configuration	With auxiliary plough	Without auxiliary plough	

Model	4506R	5506RS
Product Model	L5B450-061	L6B550-016
Mating Power/hp	210-240	240-280
Number of Plough Bodies	4+4	5+5
Tillage Width/cm	132-200	165-250
Tillage Depth/cm	20-35	20-35
Plough Body Spacing/cm	105	100
Configuration	Mirror plough body	Turnover + amplitude modulation cylinder