


AGRICULTURAL MACHINERY I NO-TILLAGE PRECISION SEEDER

LOVOL



PRODUCT INTRODUCTION


- Special bearing is used for disc soil parts which has better sealing property and long life.
- There are scrapers on the both side of the seeding discs and the scrapers on the outside adopt the tungsten steel material.
- We offered traction frame to be optional, the height from the ground are adjustable when the machine moving and transferring.
- The metering device are imported ---dedicated decice and accurate calibration.




Strengthen front beam, improve overall rigidity of skeleton beam; Equipped potash fertilizer pedal, adding fertilizer will be more convenient;



With large-size fertilizer tank, decrease the frequency of adding fertilizer;With single fertilizer clean mouth, it will be more convenient to discharge fertilizer;



Optional disc with notch or big diameter fertilizer opener, reliable quality, strong straw cutting ability, drag and heap proof,deep fertilization.



Adopting closed chain box, better dustproof effect, convenient adjustment of fertilizer amount, safe and beautiful.

TECHNICAL PARAMETERS

Model	2BMXE-2B	2BMXE-4A	2BMXE-5A
NO. OF ROW	2	4	5
ROW SPACING/CM	40-70	40-70	40-70
Working width /cm	80-140	160-280	200-350
Weight/kg	1150	1800	2450
Matched power/hp	40-60	70-100	70-100
Seed case volume/L	64	128	160
Fertilizer Tank volume /L	440+16x2	360X2+16X4	540+360+16X5
Dimension(L×W×H)M	2.97×2.0×1.48	3.44×3.4×1.48	3.75×4.01×1.48

Model	2BMXE-6B	2BMXE-7A
NO. OF ROW	6	7
ROW SPACING/CM	40-65	50-65
Working width /cm	240-390	350-455
Weight/kg	2720	2800
Matched power/hp	90-145	120-180
Seed case volume/L	192	224
Fertilizer Tank volume /L	540X2+16X6	540+360X2+16X7
Dimension(L×W×H)M	3.44×4.76×1.48	3.44×5.37×1.48